

PG21 (Consumer)

HIGH TEMP LAQUER-RESISTANT MASKING TAPE

INTERTAPE POLYMER GROUP®

TECHNICAL DATA SHEET

DESCRIPTION

A beige, high temperature fine crepe paper masking tape with a pressure-sensitive rubber/resin adhesive. Designed for clean removal from a variety of surfaces after exposure to oven temperatures up to 325°F (163°C) for 30 minutes (time and temperature determined by surface). Performs well in wet strip applications. Its easy handling, smooth crepe backing exhibits high strength, excellent conformability to irregular surfaces and exceptional cornering. Provides resistance to paint flaking and a clean, well-defined paint line.

PRODUCT APPLICATION

Automotive, truck, bus and marine paint masking. Recommended hot to warm removal, but can be removed cold.

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Backing	Fine Crepe Paper
Adhesive	Rubber/Resin
Adhesion to Steel (oz/in of width)	28 (7.7 N/25mm)
Tensile Strength (lbs/in of width)	26 (113.8 N/25mm)
Elongation (% at break)	10
Total Thickness (mils)	7.3 (0.185mm)
Quick Stick (oz/in of width)	
To Kraft	7 (1.9 N/25mm)
To Steel	16 (4.4 N/25mm)
Color	Beige



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA
 Customer Service: 800.IPG.8273 | 800.474.8273
 Tape Technical Service: 877.447.4832
www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 02/11

