

Seams Real Easy[®]

FIBERGLASS MESH DRYWALL JOINT TAPE

INTERTAPE POLYMER GROUP[®]

TECHNICAL DATA SHEET

DESCRIPTION

Adhesive-backed / self-adhering fiberglass mesh, along with permanently tacky adhesive adheres well to most surfaces under a wide range of conditions. Quick and easy to apply, and eliminates shrinkage, tears and bubbles common with paper joint tape.

PRODUCT APPLICATION

For repairing cracks, patching holes and mending seams common in plaster and drywall installation.

GOVERNMENT CONFORMANCE

ASTM D1668-80, Type III

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Backing	Woven Fiberglass Mesh
Adhesive	Acrylic
Tensile Strength (lbs/in) PST-131	120 (525 N/25mm)
Initial Adhesion to Steel (oz/in) PSTC-101	7.0 (1.9 N/25mm)
Color	White



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA
 Customer Service: 800.IPG.8273 | 800.474.8273
 Tape Technical Service: 877.447.4832
www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 9/11

