

# AC36

## 11 MIL MEDIUM GRADE DUCT TAPE

# INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

### DESCRIPTION

Polyethylene coated cloth tape with an aggressive natural rubber pressure-sensitive adhesive for improved adhesion and shear properties. Product is designed to answer the end-use / consumer need for an economical general-purpose duct tape.

### PRODUCT APPLICATIONS

HVAC applications, asbestos / lead / fiberglass abatement, exterminators, weather-proofing, gasket material for flex-duct connections, temporary wrapping, and general maintenance.

### GOVERNMENT COMPLIANCE

Meets HUD, BOCA, and L.A. county codes. Tested in accordance with UL-723.

### STORAGE RECOMMENDATION

Store new stock behind current stock. Store in a clean, dry place. Temperature of 70°F (21°C) +/- 6°F, and 40% to 50% relative humidity are recommended.

### SHELF LIFE

When stored under recommended conditions, converted rolls have an expected shelf life of up to one year from date of shipment. Jumbo rolls have the same expected shelf life but it is recommended that they are converted within 6 months of date of shipment.

### NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

<b>Backing</b>	PE Film
<b>Adhesive</b>	Natural Rubber/Resin
<b>Reinforcement</b>	PET Cloth
<b>Adhesion to Steel</b> (oz/in of width) PSTC-101	80 (21.9 N/25mm)
<b>Quick Stick to Steel</b> (oz/in of width) PSTC-5	30 (8.2 N/25mm)
<b>Tensile Strength</b> (lbs/in of width) PSTC-131	22 (96.3 N/25mm)
<b>Elongation</b> (% at break)	22
<b>Total Thickness</b> (mils) PSTC-133	11 (0.28mm)
<b>Colors</b>	Silver, Black, Red
<b>Application Temperature Range</b>	+40°F ~ +90°F (+4°C ~ +32°C)
<b>Operational Temperature Range</b>	+32°F ~ +200°F (0°C ~ +93°C)



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA

Customer Service: 800.IPG.8273 | 800.474.8273

Tape Technical Service: 877.447.4832

www.itape.com | info@itape.com



While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 02/21

