

ProMask Blue[®] Designer

14 DAY UV RESISTANT
SPECIALTY PAPER
MASKING TAPE

DESCRIPTION

A dark blue, crepe paper masking tape with a specially formulated pressure-sensitive acrylic adhesive designed for exposure to sunlight for up to fourteen days. Exhibits secure adhesion and easy, clean removal from most surfaces. Conformable. Consistent, easy unwind. Resistant to humidity and paint bleed-through.

PRODUCT APPLICATION

Wherever masking will be exposed to weather / out-of-doors conditions, interior masking of windows (where adhesive will be directly exposed to sunlight). Compatible for use on polyurethane-coated surfaces, unfinished wood, wallpaper, or new, unpainted, or freshly painted wallboard.



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA
Customer Service: 800.IPG.8273 | 800.474.8273
Tape Technical Service: 877.447.4832
www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 7/12

INTERTAPE POLYMER GROUP[®] TECHNICAL DATA SHEET

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard test. The data should not be considered as specifications.

Backing	Crepe Paper
Adhesive	Acrylic
Tensile Strength (lbs/in) ASTM D-3759	22 (96 N/25mm)
Elongation (% at break) ASTM D-3759	8
Adhesion to Steel (oz/in) ASTM D-3330	18 (4.9 N/25mm)
Total Thickness (mil) ASTM D-3652	5.8 (0.147mm)
Color	Dark Blue

