

260e+

MEDIUM DUTY REINFORCED WATER-ACTIVATED TAPE

DESCRIPTION

3-way fiberglass reinforced recycled kraft carton sealing tape manufactured with water-based adhesive.

PRODUCT APPLICATION

Used for two strip sealing cartons top and bottom. Works well on recycled cartons and non-unitized loads. Recommended for use on average weight cartons up to 50 pounds (23 kg).

ADHESION (WATER AT RECOMMENDED 110°F/43°C)

Fipago

2/0	42
2/1	61
5/0	55
15/0	58

STORAGE RECOMMENDATION

Store new stock behind current stock. Store in a clean, dry place. Temperature of 70°F (21°C) +/- 6°F, and 40% to 50% relative humidity are recommended.

SHELF LIFE

When stored under recommended conditions, converted rolls have an expected shelf life of up to two years from date of shipment. Jumbo rolls have the same expected shelf life, but it is recommended that they are converted within 6 months of date of shipment.



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA
Customer Service: 800.IPG.8273 | 800.474.8273
Tape Technical Service: 877.447.4832
www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 06/23

INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

PHYSICAL PROPERTIES

Caliper	7.6 mils (0.19mm)
MD Tensile	64 lbs/in (279 N/25mm)
CD Tensile	30 lbs/in (131 N/25mm)

CONSTRUCTION PER 3,000 SQUARE FEET (metric)

Top Ply	27 lb (44 g/m ²) Recycled Paper (100% post-consumer recycled fibers)
----------------	--

Bottom Ply	23 lb (37 g/m ²) Natural Kraft Paper (virgin fibers)
-------------------	--

Laminating Adhesive	Hot Melt
----------------------------	----------

Water-Adhesive Adhesive	Modified Starch
--------------------------------	-----------------

MD Reinforcement	(2-1-1-1-2) 75 Fiberglass (per 3"), 1/2" spacing
-------------------------	--

CD Reinforcement	(1-1-1) 150 Fiberglass, 1.10" spacing, 43 degree angle
-------------------------	--

